


General Purpose/Light Truck Casters



INDUSTRIAL GRADE

- Self-lubricating wheel bearings or roller bearings
 - Zinc finish
 - Double-ball raceways for swivel casters
- From Grainger-approved suppliers.

RIGID TOP PLATE DATA

Mount Type:	B	G	D
Bolt Hole Spacing:	31/32 x 1 1/8"	1 1/16 x 3 1/2" to 1 3/16 x 4"	1 3/4" to 2 x 5"
Mounting Bolt Dia.:	1/4"	5/16"	3/8"
Overall Size:	1 1/8 x 2 5/8"	2 1/2 x 5"	3 3/16 x 6 5/2"

SWIVEL TOP PLATE DATA

Mount Type:	A	E	F	C
Bolt Hole Spacing:	15/16 x 2 1/8"	1 3/4 x 2 5/8" to 3"	2 5/8 x 3 3/8" to 1 3/4 x 3"	3 x 4"
Mounting Bolt Dia.:	1/4"	5/16"	5/16"	3/8"
Overall Size:	1 1/8 x 2 5/8"	2 3/4 x 3 3/4"	3 3/8 x 4 1/8"	4 x 5"

Wheel Dim. (In.)	Load Rating (Lbs.)	Overall Ht. (In.)	Mount Type	SWIVEL Item No.	\$ Each	SWIVEL WITH BRAKE Mount Type	Item No.	\$ Each	RIGID Mount Type	Item No.	\$ Each	
All Rubber Soft Tread Wheel (All Black)												
2	13/16	75	2 1/2"	A	1UHH5	3.64	A	1UJH1	5.62	B	1UHJ9	3.76
2 1/2	1 1/8	120	3 1/16"	E	1UKP6	7.32	E	1UKR1	10.25	G	1UKR5	6.10
3	1 1/4	125	3 3/4"	F	1UKP7	7.86	F	1UKR2	11.06	G	1UKR6	6.29
4	1 3/4	200	5 1/8"	C	1UKP8	16.96	C	1UKR3	17.18	D	1UKR7	12.18
4	1 3/4	200	5 1/8"	C	1UKP9 *	16.96	C	1UKR4 *	20.80	D	1UKR8 *	12.18
All Polyolefin Hard Tread Wheel (All Black)												
2	13/16	100	2 5/8"	A	1UHP6	3.16	A	1UHR2	5.77	B	1UHT1	3.27
2 1/2	1 1/4	175	3 3/16"	E	1UKR9	6.54	E	1UKT3	9.76	G	1UKT6	5.47
3	1 1/4	210	3 3/4"	F	1UKT1	6.54	F	1UKT4 †	10.11	G	1UKT7	5.75
3	1 1/4	210	3 3/4"	F	1UKT2 †	7.35	F	1UKT4 †	10.11	G	1UKT8 †	7.80
All Rubber Hard Tread Wheel (All Black)												
2	13/16	100	2 5/8"	A	1UKT9	4.30	A	1UKT5	6.67	B	1UKV1	4.12
2 1/2	1 1/8	175	3 3/16"	E	1UKU1	7.63	E	1UKU6	10.78	G	1UKV2	6.10
3	1 1/4	210	3 3/4"	F	1UKU2	7.86	F	1UKU7 †	9.67	G	1UKV3	5.94
3	1 1/4	210	3 3/4"	F	1UKU3 †	8.67	F	1UKU7 †	9.67	G	1UKV4 †	9.10
4	1 3/4	300	5 1/8"	C	1UKU4	17.89	C	1UKU8	19.84	D	1UKV5	12.18
4	1 3/4	300	5 1/8"	C	1UKU5 *	21.00	C	1UKU9 *	21.38	D	1UKV6 *	16.70
Phenolic Resin Hard Tread Wheel (All Black)												
3	1 1/4	250	3 3/4"	F	1UKV7	11.44	F	1UKW1 †	14.54	G	1UKW3	10.17
3	1 1/4	250	3 3/4"	F	1UKV8 †	12.29	F	1UKW1 †	14.54	G	1UKW4 †	12.69
4	1 1/2	450	5 1/8"	C	1UKV9 *	20.31	C	1UKW2 *	23.17	D	1UKW5 *	15.32
Semi-Steel Hard Tread Wheel (All Black)												
2	15/16	125	2 5/8"	A	1UKW6	5.98	A	1UKX2	7.51	B	1UKX7	4.93
2 1/2	1	175	3 3/16"	E	1UKW7	8.47	E	1UKX3	11.97	G	1UKX8	7.69
3	1 1/4	250	3 3/4"	F	1UKW8	11.33	F	1UKX4	12.29	G	1UKX9	9.79
4	1 1/2	450	5 1/8"	C	1UKW9	24.39	C	1UKX5	32.65	D	1UKY1	20.26
4	1 1/2	450	5 1/8"	C	1UKX1 *	32.85	C	1UKX6 *	38.60	D	1UKY2 *	28.70

(*) Wheels have roller bearings. (†) NSF Certified caster. (‡) Swivel caster has 1 3/8" width wheel; rigid caster has 1 1/2" width wheel.



Swivel
No. 1UHH5



Swivel w/ Brake
No. 1UJH1



Rigid
No. 1UHJ9

Institutional Casters

shepherd casters

- Ball bearing wheel bearings
 - Zinc-plated finish
 - Double-ball raceways for swivel casters
- Nos. 2G053, 2G035, 2G059, 2G041, 2G029, and 2G047 are NSF-approved.



Bolt Hole Spacing:	1 3/4 x 2 3/4 to 3"
Mounting Bolt Dia.:	5/16"
Overall Size:	2 5/8 x 3 3/4"



Swivel with
Total-Lock
Brake
No. 2G039

Wheel Dim. (In.) Dia.	W	Load Rating (Lbs.)	Overall Ht. (In.)	Wheel Material	SWIVEL		SWIVEL WITH TOTAL-LOCK BRAKE		RIGID	
					Item No.	\$ Each	Item No.	\$ Each	Item No.	\$ Each
TPR Soft Tread/Polyolefin Hub Wheel (Gray Hub/Gray Tread)										
3	1 1/4	210	4 1/4"	TPR on Polyolefin Core	2G053	29.55	2G035	39.35	2G059	23.47
4	1 1/4	260	5 1/4"	TPR on Polyolefin Core	2G055 †	32.45	2G037 †	43.20	2G061 †	25.90
5	1 1/4	280	6 1/4"	TPR on Polyolefin Core	2G057 †	35.95	2G039 †	49.45	2G063 †	29.85
Soft Tread Wheel (Gray Hub/Gray Tread)										
3	1 1/4	250	4 1/4"	Polyurethane on Polyolefin Core	2G041	30.00	2G029	41.65	2G047	23.99
4	1 1/4	300	5 1/4"	Polyurethane on Polyolefin Core	2G043 †	33.00	2G031 †	44.70	2G049 †	26.35
5	1 1/4	315	6 1/4"	Polyurethane on Polyolefin Core	2G045 †	36.60	2G033 †	48.45	2G051 †	30.00
Soft Tread Wheel (Gray Hub/Gray Tread)										
6	1 1/4	150	7 1/4"	Natural Rubber on Polyolefin Core	3ENX3	38.15	3ENX4	41.50	3ENW6	34.70
6	1 1/4	150	7 1/4"	Natural Rubber on Polyolefin Core	3ENX5 *	36.30	3ENX6	39.65	3ENW7	34.70
6	1 1/4	300	7 1/4"	TPR on Polyolefin Core	3ENX7 †	27.60	3ENX8	30.95	3ENW8	24.91
6	1 1/4	300	7 1/4"	Polyurethane on Polyolefin Core	3ENX9	28.85	3ENY1	32.20	3ENW9	26.20
6	1 1/4	325	7 1/4"	TPE on Polyolefin Core	3ENX1	28.80	3ENX2	31.45	3ENW5	24.11

(*) Black Hub/Black Tread, (†) Thread Guards.